NOW APPROVED BY Openreach



SMAL BUT MIGHTY VERSATILE & ROBUST MINI BARRIER

The Portagate[™] is a blow moulded high density polyethylene barrier, supplied as a 3 or 4 gate system. Light and compact, the Portagate[™] is designed to meet communications industry requirements and enables increased quantities per vehicle.









PORTAGATE[™] FEATURES

CONFIGURATIONS

• Adjoining clips allow multi positioning configurations to be formed such as a triangle, a square, or a single line.



PORTAGATE [™] BARRIER SYSTEM		
DIMENSIONS	Weight	2kg (Single gate)
	Height	1000mm
	Width	750mm
STANDARDS		CH8 and Street Works Act BS 8442 (reflective only)
MATERIAL	Body	Polyethylene
	Feet	Recycled PVC



FIRM HOLD

• By sliding the top hinge clip up and down, the orientation of the panels can be locked in position to ensure added rigidity.



ADDED STABILITY

- Designed to accept anti-trip recycled feet for increased stability.
- Should there be an occurrence of broken feet, we will supply replacements at no extra cost! "subject to terms of "Surefoot" guarantee.




TEMPORARY SIGNAGE

• Recesses are included for toggle mounted courtesy signs to enable the system to be fully closed with the signs still attached.



REFLECTIVE PANEL

- Class R1 high intensity reflective.
- 20% more reflectivity than standard lower grade reflective material.
- Conforms to EN12899-1



STACKABLE

- Can be stacked open in any 180° orientation.
- Pallet stacking height is 20 units for 4 gate systems and 25 units for 3 gate systems.



BRANDING

- One-piece mould can be made in any colour to match a brand.
- Contractor details can be embossed and highlighted at the front of the barrier.







