



Cable blowing machine

Blue Dragon Jet Standard



BDJ Standard is a professional blowing machine designed for blowing micro cables. A solid and simple construction ensures easy operation and a longevity of the unit. Machine is equipped with a high quality belt feeder and pneumatic motors. Basic version has a mechanical counter meter pre-installed. Upon request we provide electronic counter with a speed measurement function.

Also available: a direction switch to retract the cable or change the blowing direction in BDJ Standard EXTENDED set-up.





BDJ Standard accessories set includes seals and bushings for every diameter of micro cable in machine's range (4.0,5.0,6.0,7.0,8.0,8.5,9.0,9.5 mm), as well as seals and bushings for micro ducts (5.0,7.0,10,12,14,16 mm)

***** Warranty 3 years!!! *****




Dane techniczne	BDJ STANDARD
Micro cable diameter	4,0 – 10,0 mm /options available: <u>2,5 and 12 mm</u>
Micro duct diameter	5 – 16 mm /option available: <u>20 mm</u>
Blowing distance / max	2500 m
Blowing speed / max	110 m/min
Work pressure / max	15 bar
Dimensions of the unit /L x W x H/	580 x 300 x 320mm / weight approx 20kg
Dimensions of the transport trunk	640 x 390 x 410mm / weight approx 33kg
Accessories included inside the set	<ul style="list-style-type: none"> • Lubricant PRELUBE 5000 (240 ml) • Pneumatic oil sample • Micro duct cutter • Set of bushings • Set of gaskets • Set of Allen keys • Socket wrench • Air hose
Required compressor's efficiency	micro ducts up till 8mm -0,8m ³ /min micro ducts 8-12mm -1,0m ³ /min micro ducts 12-16mm - 1,5m ³ /min micro ducts 15-20mm - 3,5m ³ /min



Available models of BDJ STANDARD:

<p>BDJ Standard Free of charge accessories and handy tools. Robust mechanical cable length counter.</p>		
<p>BDJ Standard Extended including a directional switch and an extended blowing head!</p> <p>The direction switch allows you to change the blowing direction and withdraw the cable from the micro duct. <u>Standard Extended blowing range:</u> 2.5-12 mm micro cable 5-20 mm micro duct</p>	 <p>BDJ Standard with a direction switch and a mechanical counter meter</p>	 <p>BDJ Standard with a direction switch</p>

Our recommendations!

	<p>Cable twister/ coiling/cable storing device</p> <p>Carousel is a useful device to store the excess of a cable while blowing-in cables in two directions, protects the cable from damaging, helps laying long sections of cable, foldable capacity up till 2000m of cable d=5-8mm</p>
	<p>Prelube liquids – reduce friction and extend the blowing distance</p> <p>Pneumatic oil for the engines –a necessity in the operation of the blowing machine, consumable material</p>
	<p>Bullets for micro duct calibration (5, 7, 8 mm)</p>

*** WWW.FIBERBLOWINGMACHINES.EU ***